

Mobile washing unit without foam system from 20 to 200 Bar

3.2



Entirely designed and produced by **VEMA** with an eye on the cleaning needs of a various range of sectors, this unit represents a mix of exceptional safety, functionality, power, efficiency and durability. **The pressure can be adjusted from 20 to 200 bars with flow rates of from 15 to 21 l/min.**

The machine is fitted with a support for manual hose reel (optional), also available with 15 mt. high pressure hose, practical stainless steel lance with pull-out trigger gun, support for a 15 kg detergent container and reliable detergent dispenser system.

The ease of movement thanks to the four wheels, delayed total stop device activated by closing the lance with zeroing of pressure in the delivery hose, high maneuverability of the **low voltage (24 V) machine controls**, special seal system suitable for hot water even at a temperature of more than **80°C** and attractive elegant design make this great little washing machine the best answer to all the indoor and outdoor cleaning needs of every company.

FDR Base

PRESSURE FROM 20 TO 200 BAR

Mobile washing unit without foam system from 20 to 200 Bar

3.2

Available configurations

CODE	MAX. FLOW RATE (lt/min)	ADJUSTABLE PRESSURE (Bar)	POWER (KW)	POWER SUPPLY (Volt)	RPM	WEIGHT (kg)	*DIMENSIONS (LxHxP) mm	MAX. IN-LET TEMPERATURE	MAX. N° OF USERS
10.3513.00*	15	20 - 200	5,5	400	1450	82	550x850x1000	75°C	1
10.3514.00*	21	20 - 150	5,5	400	1450	92	550x850x1000	75°C	1
*Same as model 10.3513.00 but with fitted automatic hose reel									
10.3515.00	15	20 - 200	5,5	400	1450	87	550x1000x1000	75°C	1
10.3516.00	21	20 - 150	5,5	400	1450	97	550x1000x1000	75°C	1
* Same as model 10.3514.00 but with fitted automatic hose reel									

Technical features

- Low voltage controls (24 volt)
- Total stop
- Motor protection circuit breaker
- Over temperature 80° C safety control
- Pressure adjustment
- Pressure indicator
- Pressure and flow controls
- Pump with ceramic pistons and s/s valve
- IP55 control panel
- Chemical suction in L.p. by injector
- S/s frame
- Dosing system
- Chemical distribution in Low pressure
- Cover in preformed Abs
- Detergent tank 25 kg

Supplied accessories



90 cm stainless steel athermic lance without nozzle - gun ST2300 Sw
Sec 9.6 - Cod. 10.3532.00



S/s Nozzle 1/4"
Sec. 9.7



Supporto inox per tubi
Sec. 9.17 - Cod. 10.1335.00



H.p. hose R/2 L= 15mt.
crimped 3/8" zinc female.
Sec. 9.10 - Cod. 10.3474.00