

Wall mounted High Pressure Washing machine 130 Bar Max

1.2



The **Hydra 130/12** truly represents a next-level solution among the high pressured ones. Unique in its sector for **compactness, low noise levels, reliability and standard accessories**, it allows foaming, rinsing and disinfection processes to be optimised. The system already incorporates all components, from the electrical panel to the **100% stainless steel dispensing system** for foaming and disinfection, creating a highly reliable integrated combination to satisfy all sanitising needs. The frame is in stainless steel and all parts of the machine can be easily inspected for servicing and control. The pump absorbs just **3 kW**, produces a pressure of about **130 bars** with a **flow rate of 12 l/min** and is suitable for use with hot water up to **75°C**. The controls are low voltage (**24 V**) and a delayed total stop function shuts down the system when the lance is closed. The **Hydra 130/12** is also one of the most rational washing machines to use as the operator just need to turn the knob on the front panel and insert the lance.

Available configurations

CODE	MAX.FLOW RATE (lt/min)	ADJUSTABLE PRESSURE (Bar)	POWER (KW)	VOLTAGE (Volt)	RPM	WEIGHT (Kg)	DIMENSIONS LxHxP (mm)	MAX. IN-LET TEMPERATURE	MAX. N° OF USERS
10.3729.00	12	20 - 130	3	400	1450	50	610x350x350	75 °C	1

Technical features

- S/s frame
- S/s dosing system Foam System 1 for foam and disinfection.
- IP65 control panel
- Pump with 3 ceramic pistons complete of special seals kit for high temperature
- Controls by flow sensor
- Pressure adjustment
- Pressure indicator
- Over temperature 75 ° C safety controls
- Total stop

Supplied accessories

1.2



S/s Washing lance cm 70 without nozzle complete of pin Ø14 **Sec. 9.4 - Cod. 10.2219.00**



S/s nozzle 1/8"
Sec. 9.7



Gun with coupling Ø 14
Sec. 9.9 - Cod. 10.1364.00



Hose H.P. R/2 15mt. Non-staining
3/8" female zinc-plated fittings
Sec. 9.10 - Cod. 10.3534.00



S/s wall holder for hose
Sec 9.17 - Cod. 10.1335.00



S/s mounting bracket
Cod. 20.2073.06 + Cod. 20.0707.06
(Only wall model)



Foam Lance Ø 1
Sec. 9.8 - Cod. 10.2218.00

Optional accessories



S/S Stainless Steel
Manual Hose Reel 20 mt
Sec. 9.2 - cod. 10.1495.00 -R/X
cod. 10.3488.00 -R/Z



S/S Automatic Hose Reel
High Pressure 20 mt
Sec. 9.1
cod. 10.5007.00 -R/Z
cod. 10.5019.00 -R/X

R/X: Stainless steel press fitting pipe
R/Z: Galvanized press fitting pipe